


# WEST JORDAN CITY

# WELL # 8 PUMP BUILDING CONSTRUCTION PLANS MARCH 2023



BRUSH FORK DRIVE

PROJECT
LOCATION

RON WOOD PARK

PROJECT LOCATION
6183 WEST 8600 SOUTH

APPROVED BY PLANNING DEPARTMENT BY: LARRY GARDNER — CITY PLANNER 01/19/2023

CONDITIONAL USE PERMIT APPROVED BY WJ PLANNING COMMISSION 08/18/2020



### WEST JORDAN CITY OFFICIALS

MAYOR
DIRK BURTON
CITY COUNCIL
PAMELA BLOOM
KELVIN GREEN
ZACH JACOB
CHRIS MCCONNEHEY
DAVID PACK
KAYLEEN WHITELOCK
MELISSA WORTHEN

#### HANSEN, ALLEN & LUCE DESIGN TEAM

MARVIN E. ALLEN, P.E. — PRINCIPAL

MARK G ATENCIO, P.E. — PROJECT MANAGER

ZAK C. STEELE — PROJECT ENGINEER

ROBERT C. CONDER, S.E. — STRUCTURAL ENGINEER

(CONDER ENGINEERING)

KEITH B. HEGERHORST, P.E. — ELECTRICAL ENGINEER


859 W. SOUTH JORDAN PKWY STE. 200 SOUTH JORDAN UTAH, 84095 (801) 566-5599


(HPE, INC. ELECTRICAL ENGINEERS)
TAYLOR E. GROBERG, P.E.

TAYLOR E. GROBERG, P.I (BLUEFIELD ENGINEERING)

ERIC LYMAN — LANDSCAPE ARCHITECT (E.A. LYMAN LANDSCAPE ARCHITECTS)

JAY R. MCQUIVEY — GEOTECHNICAL (AGEC, INC.)





REVISIONS

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

© 202

EGERHORST POWER ENGINEERING INCORPORATED

708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORS

#### GENERAL NOTES

- . VERIFY ALL EQUIPMENT DIMENSIONS AND LOCATIONS BEFORE BEGINNING ROUGH—IN. CONSULT ALL APPLICABLE CONTRACT DRAWINGS AND SHOP DRAWINGS TO ENSURE NEC CODE CLEARANCE REQUIRED AROUND ALL ELECTRICAL EQUIPMENT.
- CONTRACTOR SHALL VERIFY ALL ELECTRICAL LOADS (VOLTAGE, PHASE, CONNECTION REQUIREMENTS, ETC.) OF EQUIPMENT FURNISHED BEFORE BEGINNING ROUGH—IN.
- 3. SEE APPLICABLE SHOP DRAWINGS FOR ROUGH-IN LOCATION OF ALL EQUIPMENT, WIRING DEVICES, ETC.
- 4. THE ELECTRICAL CONTRACTOR SHALL NOTIFY AND COOPERATE WITH THE MECHANICAL CONTRACTOR SUCH THAT NO PIPING, OR EQUIPMENT FOREIGN TO THE OPERATION OF THE ELECTRICAL EQUIPMENT SHALL BE PERMITTED TO BE INSTALLED IN, ENTER OR PASS THROUGH ELECTRICAL ROOMS OR SPACES; OR ABOVE OR BELOW ELECTRICAL EQUIPMENT IN THE OTHER AREAS.
- 5. ALL PENETRATIONS OF FLOORS, WALLS AND CEILINGS SHALL BE SEALED WITH APPROVED MATERIAL.
- 5. FOR PACKAGE EQUIPMENT PROVIDED ON THE PROJECT, SOME CONDUITS AND WIRES ARE SHOWN ON THE DRAWINGS, BUT IT IS EXPECTED THAT SOME ADDITIONAL CONDUITS AND WIRES MAY BE REQUIRED BY EQUIPMENT MANUFACTURERS TO COMPLETE INSTALLATION. IT IS INCUMBENT UPON THE GENERAL CONTRACTOR TO COORDINATE THIS REQUIREMENT WITH HIS SUBCONTRACTORS TO MAKE SURE THAT EQUIPMENT SUPPLIER PROVIDED ALL NECESSARY ELECTRICAL INFORMATION TO ELECTRICAL SUBCONTRACTOR FOR INCLUSION WHETHER SHOWN OR NOT SHOWN ON THE DRAWINGS.
- 7. IF OTHER THAN FIRST NAMED EQUIPMENT IS USED, IT SHALL BE CAREFULLY CHECKED FOR ELECTRICAL REQUIREMENTS AND CONTROL REQUIREMENTS OF ALTERNATE EQUIPMENT. SHOULD CHANGES OR ADDITIONS OCCUR IN ELECTRICAL WORK, OR THE WORK OF OTHER CONTRACTORS BE REVISED BY THE ALTERNATE EQUIPMENT, THE COST OF ALL CHANGES SHALL BE BORNE BY THE ELECTRICAL CONTRACTOR.

WEST JORDAN

WEST JORDAN CITY WELL #8 ELECTRICAL LEGEND

E001 089.29.100

IGNED KBH

RAFTED DAS

HECKED KBH

DATE AUGUST 2020

#### CONDUIT/CONDUCTOR SCHEDULE THHN, THWN, THWN-2 DRAWING CONDUCTOR MIN. CONDUIT SIZE AMP RATING ID TAG. QTY.\* SIZE SIZE EXCEPTIONS 3/4" 20 #12 3/4" 312 3 3/4" 412 4 20 2 3/4" 30 30 3 #10 3/4" 40 3/4" 28 3/4" #8 3/4" 50 38 3 48 4 3/4" 26 3/4" 36 3/4" 3 46 3/4" 4 3/4" 1" 1" 1"(C2,C9) 24 2 3/4"(C4),1-1/4"(C9) 1-1/4"(C9) 85 34 44 4 22 2 1-1/4"(C9) 115 32 #2 3 1-1/4" 42 4 1"(C3,C4) 1"(C3) 21 | 1–1/4"| 130 31 3 1-1/4" 1-1/4" 1-1/2"(C2,C9,C10) 41 210 1-1/4" 1-1/2"(C3,C9) 1-1/4" 1/0 150 310 3 2"(C9) 1-1/2"(C3,C4,C9) 410 4 1-1/2" 220 2 1-1/4" 320 1-1/2" 3 420 1-1/2" 1-1/4(C4) 230 2"(C3,C9) 200 3/0 330 3 1-1/2" 430 4 2"(C3) 240 1-1/2" 230 4/0 340 3 2-1/2"(C9) 440 4 1-1/2"(C4) 2-1/2"(C1,C8) 2"(C4) 225 250 255 325 KCMIL 425 2-1/2" 2-1/2"(C9) 235 2" 350 2-1/2" 3" 2"(C4) 310 335 3 KCMIL 2-1/2"(C1,C4) 435 4 2"(C4) 250 2-1/2" 500 2-1/2"(C1,C4) 380 350 3 4 KCMIL 450 3-1/2"(C9) 275 2 375 3 475 4 XFANDER 3" 3" 3"(C1,C7,C8) 4" 3-1/2"(C1,C4,C8) 475

\* CONDUCTOR QUANTITY DOES NOT INCLUDE GROUNDING CONDUCTORS. SEE EQUIPMENT GROUNDING CONDUCTORS FOR

WHERE: C1 = ELECTRICAL METALLIC TUBING

C2 = ELECTRICAL NON-METALLIC TUBING

C3 = FLEXIBLE STEEL CONDUIT

C4 = INTERMEDIATE METALLIC CONDUIT

C7 = LIQUIDTIGHT FLEXIBLE METAL CONDUIT

C8 = RIGID METALLIC CONDUIT

C9 = PVC SCHEDULE 80 CONDUIT

C10 = PVC SCHEDULE 40 CONDUIT

GROUNDING ELECTRODE CONDUCTOR SERVICE ENTRANCE OR SEPARATELY DERIVED SYSTEM

COPPER	WIRE
CONDUCTOR	SIZE
#2 OR	#8
SMALLER	" -
1 OR 1/0	#6
2/0 OR 3/0	#4
>3/0 THRU	#2
350 KCMIL	π-
>350 KCMIL	
THRU 600	1/0
KCMIL	

#### **EQUIPMENT GROUNDING** CONDUCTORS

USE OR CB	SIZE
SIZE	(COPPER)
15	14
15 20	14 12 10 10
30	10
40	10
60	10
100	8
200	6
300	8 6 4 3 2
400	3
500	2
600	1
800	1/0
1000	2/0
1200	2/0 3/0
1600	4/0
2000	250
2500	350

#### WEST JORDAN WELL TAG LIST HVAC EQUIPMENT

TAG	DESCRIPTION	LOCATION	SUPPLIED BY	INSTALLED BY		
CU-1	CONDENSING UNIT 1	OUTSIDE	CONTRACTOR	CONTRACTOR		
CU-2	CONDENSING UNIT 2	OUTSIDE	CONTRACTOR	CONTRACTOR		
EF-1	EXHAUST FAN	CHLORINE ROOM	CONTRACTOR	CONTRACTOR		
FC-1	FAN COIL 1	WELL ROOM	CONTRACTOR	CONTRACTOR		
FC-2	FAN COIL 2	WELL ROOM	CONTRACTOR	CONTRACTOR		
LA-1	EXHAUST FAN INTAKE LOUVER ACTUATOR	CHLORINE ROOM	CONTRACTOR	CONTRACTOR		
LA-2	EXHAUST FAN LOUVER ACTUATOR	CHLORINE ROOM	CONTRACTOR	CONTRACTOR		
UH-1	UNIT HEATER	WELL ROOM	CONTRACTOR	CONTRACTOR		
UH-2	ÙNIT HEATER	CHLORINE ROOM	CONTRACTOR	CONTRACTOR		

DUMB AND FOUTDMENT

	PUMP AND E	QUIPMENT		
TAG	DESCRIPTION	LOCATION	SUPPLIED BY	INSTALLED BY
ATS	AUTOMATIC TRANSFER SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR
CP-1	MAIN CONTROL PANEL	WELL ROOM	CONTRACTOR	CONTRACTOR
CP-2	EXHAUST FAN CONTROL PANEL	WELL ROOM	CONTRACTOR	CONTRACTOR
CTE	CURRENT TRANSFORMER ENCLOSURE	OUTSIDE	CONTRACTOR	CONTRACTOR
GA-1	GATE ACTUATOR	OUTSIDE	CONTRACTOR	CONTRACTOR
GEN	BACKUP POWER GENERATOR	OUTSIDE	CONTRACTOR	CONTRACTOR
MSD	MAIN SERVICE DISCONNECT	OUTSIDE	CONTRACTOR	CONTRACTOR
P-1	WELL PUMP	WELL ROOM	CONTRACTOR	CONTRACTOR
TC-1	TABLET CHLORINATOR	CHLORINE ROOM	CONTRACTOR	CONTRACTOR
RTU	REMOTE TELEMETRY UNIT	WELL ROOM	OWNER	CONTRACTOR
VFD	WELL VARIABLE FREQUENCY DRIVE	WELL ROOM	CONTRACTOR	CONTRACTOR

#### SWITCHES

TAG	DESCRIPTION	LOCATION	SUPPLIED BY	INSTALLED BY	
LSH-1	PUMP ROOM FLOOR HIGH WATER SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR	
PSH-1	WELL PUMP DISCHARGE PRESSURE SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR	
ZS-1	MAN-DOOR POSITION SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR	
ZS-2A	SERVICE DOOR POSITION SWITCH	WELL ROOM	CONTRACTOR		
ZS-2B	SERVICE DOOR POSITION SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR	
ZS-3	WELL ROOF HATCH POSITION SWITCH	WELL ROOM	CONTRACTOR	CONTRACTOR	
ZS-4	MAN-DOOR POSITION SWITCH	CHLORINE ROOM	CONTRACTOR	CONTRACTOR	
ZS-5B	WV-1 IN FULL WASTE POSITION	WELL ROOM	CONTRACTOR	CONTRACTOR	
ZS-5A	WV-1 IN FULL SYSTEM POSITION	WELL ROOM	CONTRACTOR	CONTRACTOR	

#### INSTRUMENTS

TAG	DESCRIPTION	LOCATION	SUPPLIED BY	INSTALLED BY	
AE-3	CHLORINE ANALYZER	CHLORINE ROOM	CONTRACTOR	CONTRACTOR	
AE-2	TURBIDITY ANALYZER	WELL ROOM	CONTRACTOR	CONTRACTOR	
AIT-3	CHLORINE INDICATOR/TRANSMTTER	WELL ROOM	CONTRACTOR	CONTRACTOR	
AIT-2	TURBIDITY INDICATOR/TRANSMITTER	WELL ROOM	CONTRACTOR	CONTRACTOR	
FE-1	WELL DISCHARGE FLOW ELEMENT	WELL ROOM	CONTRACTOR		
FIT-1	WELL DISCHARGE FLOW INDICATOR/TRANSMITTER	WELL ROOM	CONTRACTOR	CONTRACTOR	
LT-1	WELL LEVEL TRANSMITTER	WELL ROOM	CONTRACTOR	CONTRACTOR	
PT-1	STATION DISCHARGE PRESSURE TRANSMITTER	WELL ROOM	CONTRACTOR	CONTRACTOR	
PT-2	WELL DISCHARGE PRESSURE TRANSMITTER	WELL ROOM CONTRACTOR		CONTRACTOR	
TT-1	ROOM TEMPERATURE TRANSMITTER	WELL ROOM CONTRACTOR		CONTRACTOR	
TT-2	ROOM TEMPERATURE TRANSMITTER	CHLORINE ROOM	CONTRACTOR	CONTRACTOR	

#### VALVES

TAG	DESCRIPTION	LOCATION	SUPPLIED BY	INSTALLED BY
V-1	WASTE VALVE	WELL ROOM	CONTRACTOR	CONTRACTOR
SV-1	WELL PRE-LUBE SOLENOID VALVE	WELL ROOM	CONTRACTOR	CONTRACTOR
SV-2	TURBIDITY ANALYZER VALVE	WELL ROOM	CONTRACTOR	CONTRACTOR
SV-3	CHLORINE ANALYZER VALVE	WELL ROOM	CONTRACTOR	CONTRACTOR
V-2	SYSTEM VALVE	WELL ROOM	CONTRACTOR	CONTRACTOR

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEM

© 2020

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST


#### **GENERAL NOTES:**

1. NOT USED.

### **SHEET KEYNOTES:**


1. NOT USED.














H.P.E. INC. ELECTRICAL ENGINEERS

© 2020

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025 FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORS

#### **GENERAL NOTES:**

- 1. FOR CONDUIT AND CONDUCTOR REQUIREMENTS REFER TO ONE-LINE DIAGRAM AND/OR THE PANEL SCHEDULES FOR THE CIRCUIT ID. WIRE AND CONDUIT REQUIREMENTS ARE ON THE CONDUIT/CONDUCTOR TABLE ON E002.
- EQUIPMENT ARRANGEMENT SHOWN IS APPROXIMATE. CONTRACTOR SHALL ADJUST LOCATION AS REQUIRED FOR THE DIMENSIONS OF THE ACTUAL EQUIPMENT. MAINTAIN NEC CLEARANCES AS REQUIRED.
- 3. SPECIFIED INDOOR UNITS RECEIVE POWER FROM OUTDOOR UNITS THROUGH FIELD—SUPPLIED INTERCONNECTED WIRING. IF UNITS ARE OTHER THAN SPECIFIED, MODIFY PROVIDE POWER AS REQUIRED.
- 4. HEATING CONTROLS BY MECHANICAL CONTRACTOR. CHLORINE ROOM EXHAUST FAN CONTROLS BY ELECTRICAL CONTRACTOR.
- 5. VERIFY LOCATIONS OF ALL ELECTRICAL CONNECTIONS PRIOR TO CONDUIT ROUGH—IN.

#### **SHEET KEYNOTES:**

- 1. CONTRACTOR SHALL PROVIDE AND INSTALL A 24"H x 20"W x 8"D LOCKABLE NEMA 12 ENCLOSURE FOR THE LANDSCAPE TIMER AND OUTLET. COORDINATE WITH LANDSCAPE CONTRACTOR DURING CONSTRUCTION AND MODIFY DIMENSIONS AS REQUIRED FOR IRRIGATION TIMER. INSTALL A 2"C FROM THE ENCLOSURE UNDER THE PAVING TO THE LANDSCAPE AREA FOR THE IRRIGATION VALVE CONTROL WIRES.
- 2. INSTALL FLOW METER INDICATOR/TRANSMITTER ON THE WALL BELOW THE FAN COIL UNIT.
- INSTALL THE SECURITY ENCLOSURE BELOW THE RTU RADIO ENCLOSURE AND AT THE SAME HEIGHT AS CP-1.
- 4. SCADA RADIO ENCLOSURE: 24"H X 20"W X 8"D ENCLOSURE WITH INTERNAL PANEL. DATA RADIO AND ANTENNA SURGE DEVICE PROVIDED AND INSTALLED BY
- 5. FLOOR MOUNTED EQUIPMENT: EXTEND HOUSEKEEPING PAD 4—IN IN FRONT AND SIDES. WALL MOUNTED EQUIPMENT: PAD SHALL EXTEND 6—IN (MAX.) FROM


HANSEN ALLEN & LUCE<sub>nc</sub>

RAFTED DAS HECKED KBH ATE AUGUST 2020 REVISIONS





089.29.100



H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEM

© 2020

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025 FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

**GENERAL NOTES:** 

1. VERIFY LOCATIONS OF ALL DEVICES PRIOR TO CONDUIT

2. FOR WIRE AND CONDUIT REQUIREMENTS, REFER TO INSTRUMENTATION AND CONTROL ONE—LINE DIAGRAM ON

#### **SHEET KEYNOTES:**

- 1. GROUND ANTENNA SUPPORT WITH AWG NO 6 BC. INSTALL TWO 3/4"X10' GROUND RODS APPROXIMATELY 10' APART.
- 2. SUPPLY AND INSTALL A 20"W x 24"H x 10"D RTU RADIO ENCLOSURE WITH A SUB PANEL. PROVIDE PANEL TO SCADA CONTRACTOR FOR ASSEMBLY OF THE RTU. RTU COMPONENTS PROVIDED AND INSTALLED BY APCO.
- 3. SECURITY ENCLOSURE INSTALLED BELOW RTU ENCLOSURE.
- 4. FOR A FUTURE CAMERA, INSTALL A RECESSED CCTV J-BOX IN THE BUILDING WALL 6-IN BELOW SOFFIT CENTERED ABOVE THE GENERATOR.
- 5. INSTALL BUILDING END J-BOXES AT SAME HEIGHT AS THE SIDE J-BOXES.
- 6. RECESS 2X4 ELECTRICAL BOX IN MASONRY FOR CARD READER. VERIFY HEIGHT AND LOCATION WITH OWNER DURING CONSTRUCTION.

HANSEN ALLEN & LUCEnt


RAFTED DAS HECKED KBH ATE AUGUST 2020 REVISIONS



SHOWN

WEST JORDAN CITY WELL #8 **ELECTRICAL** PUMP HOUSE INSTR. & CONTROL PLAN

E103 089.29.100



H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

HPE PROJECT 20.025

**GENERAL NOTES:** 

1. REFER TO PANEL SCHEDULE FOR WIRE AND CONDUIT SIZES.

#### **SHEET KEYNOTES:**

- THREE-WAY SWITCHES AND FOUR-WAY SHALL CONTROL BOTH ROOM FIXTURES AT THE SAME TIME.
- 2. EXHAUST FAN MANUAL SWITCH (HS-1) LABEL AS CHLORINE ROOM EXHAUST FAN.
- PROVIDE A PILOT LIGHT TOGGLE SWITCH TO CONTROL THE TWO GENERATOR FLOOD LIGHTS. LABEL "GENERATOR FLOOD LIGHTS".
- 4. RELOCATE FIXTURE AS REQUIRED FOR ROOF HATCH.
- 5. PROVIDE A 90-MINUTE BATTERY PACK IN THIS FIXTURE
- 6. INSTALL FIXTURE 8-IN ABOVE DOOR.


HANSEN ALLEN & LUCEnc

RAFTED DAS AS SHOWN HECKED KBH DATE AUGUST 2020 REVISIONS

**WEST JORDAN** 

WEST JORDAN CITY WELL #8 **ELECTRICAL** PUMP HOUSE LIGHTING PLAN

E104 089.29.100



H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

HPE PROJECT 20.025

**GENERAL NOTES:** 

1. REFER TO PANEL SCHEDULE FOR WIRE AND CONDUIT SIZES.

#### **SHEET KEYNOTES:**

- THREE-WAY SWITCHES AND FOUR-WAY SHALL CONTROL BOTH ROOM FIXTURES AT THE SAME TIME.
- 2. EXHAUST FAN MANUAL SWITCH (HS-1) LABEL AS CHLORINE ROOM EXHAUST FAN.
- PROVIDE A PILOT LIGHT TOGGLE SWITCH TO CONTROL THE TWO GENERATOR FLOOD LIGHTS. LABEL "GENERATOR FLOOD LIGHTS".
- 4. RELOCATE FIXTURE AS REQUIRED FOR ROOF HATCH.
- 5. PROVIDE A 90-MINUTE BATTERY PACK IN THIS FIXTURE
- 6. INSTALL FIXTURE 8-IN ABOVE DOOR.

HANSEN ALLEN & LUCEnc

RAFTED DAS AS SHOWN HECKED KBH DATE AUGUST 2020 REVISIONS

**WEST JORDAN** 

WEST JORDAN CITY WELL #8 **ELECTRICAL** PUMP HOUSE LIGHTING PLAN


E104 089.29.100


H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS HEGERHORST POWER ENGINEERING INCORPORAT 708 EAST 50 SOUTH AMERICAN FORK, UT 84003


© 202


HPE PROJECT 20.025

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST












CONDUIT THRU EXISTING WALL B


WELDED GROUND CONNECTION C

FLOW METER GROUNDING DETAIL D









CHLORINE ROOM SWITCHES F

POLE BASE DETAIL E




HANSEN ALLEN & LUCE...

DATE AUGUST 2020	NO.	DATE	REVISIONS	BY	APVD.	
CHECKED <b>KBH</b>	1					
DRAFTED DAS	2					ı
DESIGNED KBH	3					ı



SCALE



HANSEN ALLEN & LUCEne

PROJECT ENGINEER

ESIGNED KBH RAFTED DAS CHECKED KBH DATE AUGUST 2020 DATE REVISIONS

BY APVD




SHOWN

WEST JORDAN CITY WELL #8 **ELECTRICAL** DETAILS, SHT. 2


SHEET E502

089,29,100




#### NOTES:


- SITE PREPARATION: ALL DIRT BENEATH THE PAD SITE MUST BE COMPACTED AND LEVEL PRIOR TO SETTING OR POURING THE PAD TO PREVENT SETTLING.
- 2. CONCRETE: SHALL BE MADE USING A STANDARD BRAND OF PORTLAND CEMENT. STEEL REINFORCEMENT SHALL BE #4 REBAR PLACED ACCORDING TO THE DRAWINGS. THE PAD MUST BE POURED AT LEAST THREE FULL DAYS PRIOR TO SETTING THE UNIT. CONCRETE MUST BE KEPT ABOVE FREEZING AT LEAST 72 HOURS AFTER POURING. THE FINISHED SURFACE MUST BE COMPLETELY FLAT AND LEVEL. ALL WORK MUST BE DONE TO HIGH QUALITY STANDARDS.
- 3. <u>Prefabrication</u>: The PAD MAY Either be constructed on the site or prefabricated according to specifications. Prefabricated PADS SHALL BE SET LEVEL AND PLUMB.
- 4. TRANSFORMER CONDUIT WINDOW LAYOUT: LOW VOLTAGE CONDUITS SHALL BE FORMED AS TIGHTLY AS POSSIBLE AGAINST RIGHT SIDE OF THE OPENING AND SHALL IN NO CASE EXTEND FURTHER THAN 16" FROM THE RIGHT SIDE OF CONDUIT WINDOW ON THE PAD, NO MORE THAN 4 CONDUITS WILL BE USED ON THE LOW VOLTAGE SIDE. DO NOT PUT ANY CONCRETE IN OR UNDER THE CONDUIT WINDOW. USE DIRT TO SEPARATE CONDUITS. BELL ENDS ARE REQUIRED FOR ALL METAL CONDUITS BUT NOT FOR PLASTIC CONDUITS.
- 5. <u>CLEARANCE</u>: THE FRONT OF THE PAD SHOULD ALWAYS FACE AWAY FROM ADJACENT STRUCTURES AND BE FREE OF OBSTRUCTIONS. AT LEAST THREE FEET MUST SEPARATE THE EDGES OF THE PAD FROM ANY ADJACENT STRUCTURES. THE EDGES OF THE PAD MUST BE AT LEAST TEN FEET FROM ANY COMBUSTIBLE STRUCTURE. THE AREA IN FRONT OF THE PAD MUST HAVE TEN FEET OF CLEAR LEYEL WORKING AREA FOR MAINTENANCE OF THE UNIT.



## PRIMARY CONDUIT TRENCH B



# SECONDARY CONDUIT TRENCH C



TRENCH DETAIL D



ITY TRANSFORMER PAD A

SIGNED KBH RAFTED DAS HECKED KBH DATE AUGUST 2020 REVISIONS



DETAILS, SHT. 3

E503 089.29.100

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEM

1. REFER TO UTILITY STANDARD DETAILS ON—LINE FOR THE LATEST PAD AND TRENCH REQUIREMENTS.

© 202

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

**GENERAL NOTES:** 

SHEET KEYNOTES:


FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORS


HPE PROJECT 20.025

2. NOT USED.


1. NOT USED.

WEST JORDAN CITY WELL #8 **ELECTRICAL** 











| Size | EMI | RGS | EMI/RGS | EMI/RGS | FINT | FIN 3-1/2" P1120 P1120 -4" P1121 P1121 -\* = SUPPLIED WITH SLOTTED HEAD SCREW AND NUT

CONDUIT CLAMP INSTALLATION D



SUPPORT BASE INSTALLATION C



BASE ANCHOR INSTALLATION E

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

© 2020

HPE PROJECT 20.025 FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORS

**GENERAL NOTES:** 

1. NOT USED.

**SHEET KEYNOTES:** 

1. NOT USED.

SIGNED **KBH** RAFTED DAS HECKED KBH DATE AUGUST 2020 REVISIONS



WEST JORDAN CITY WELL #8 **ELECTRICAL** DETAILS, SHT. 4

E504 089.29.100

HANSEN ALLEN & LUCEnc





#### **GENERAL NOTES:**

1. NOT USED.


#### **SHEET KEYNOTES:**

1. NOT USED.





JUNCTION BOX CONDUIT PENETRATION DETAIL




- PULL SLOT

PULL SLOT

#### **BOX AND LID DIMENSIONS**

BOX TYPE	"H" inch	"L" inch	"T" inch	"W" inch	"X" inch	"Y" inch	"Z" inch
I-PC	24	25	1 1/2	16	23 1/4	13 ¾	2
II-PC	24	37 %	1 ½	26	35 %	24	3
III-PC	24	49 %	2	32 %	47 %	30 1/8	3



JUNCTION BOX CONCRETE COLLAR DETAIL

### STAMP BOX LOGO INTO THE LID FROM THE FACTORY. (SEE STANDARD SPECIFICATION 13554).

NOTES:

- 2. DO NOT PLACE JUNCTION BOXES IN THE TRAVELED WAY OR ON FREEWAY SHOULDERS.
- CONCRETE COLLAR WIDTH VARIES WHEN ADJACENT TO ATMS CABINETS. REFER TO AT AND SL SERIES STD DWGS,
- 4. PROVIDE CONCRETE COLLARS EXCEPT WITHIN CONCRETE PAVED AREAS.
- 5. INSTALL CONDUIT PLUG PER STANDARD SPECIFICATION 13554. 6. ALIGN ATMS CONDUIT BY COLOR ON EACH SIDE OF THE JUNCTION BOX.
- 7. PROVIDE TYPE III-PC JUNCTION BOXES WITH A SPLIT LID.
- 8. CONFORM TO ANSI/SCTE-77 2007 "SPECIFICATION FOR UNDERGROUND ENCLOSURE INTEGRITY" TIER 22 LOADING FOR ALL JUNCTION BOXES,
- 9. EXTEND GROUND ROD A MINIMUM OF 4 INCHES AND A MAXIMUM OF 6 INCHES ABOVE BOTTOM OF JUNCTION BOX.
- USE A SPLIT BOLT TO ATTACH GROUND WIRES TO GROUND ROD. ATTACH NOT MORE THAN TWO WIRES PER BOLT.
- 11. DO NOT CUT GROUND RODS.

UG ELECTRICAL BOX A


HANSEN ALLEN & LUCEnc

RAFTED DAS HECKED KBH DATE AUGUST 2020 REVISIONS



WEST JORDAN CITY WELL #8 **ELECTRICAL** DETAILS, SHT. 5

E505 089.29.100



THE THE THE	-11			
ROCKY MOUNTAIN POWER				
AUBREY RASMUSSEN	JBREY RASMUSSEN			
PHONE: 801-576-624	7			
6845352				
SUPPLIED BY:	INSTALLED BY:			
-	CONTRACTOR			
CONTRACTOR	CONTRACTOR			
UTILITY COMPANY	UTILITY COMPANY			
SUPPLIED BY:	INSTALLED BY:			
CONTRACTOR	CONTRACTOR			
UTILITY COMPANY	UTILITY COMPAN			
SUPPLIED BY:	INSTALLED BY:			
-	CONTRACTOR			
	CONTRACTOR			
UTILITY COMPANY	UTILITY COMPANY			
SUPPLIED BY:	INSTALLED BY:			
	UTILITY COMPANY			
CONTRACTOR	CONTRACTOR			
-	-			
CONTRACTOR	CONTRACTOR			
UTILITY COMPANY	UTILITY COMPANY			
CONTRACTOR	CONTRACTOR			
•				
SUPPLIED BY:	INSTALLED BY:			
CONTRACTOR	CONTRACTOR			
-	-			
	AUBREY RASMUSSEN PHONE: 801-576-624 6845352  SUPPLIED BY: CONTRACTOR UTILITY COMPANY SUPPLIED BY: CONTRACTOR UTILITY COMPANY SUPPLIED BY: CONTRACTOR UTILITY COMPANY CONTRACTOR			

PROJECT ENGINEER

B	Phase and Voltage	New Load	Load to be	Total Connected	***
Description	4 771 400 (040 77	to be added	removed	Load after changes	Un
HVAC (name plate rating)	1 Phase 120/240 V	1.8	-	1.8	Ton
Refrigeration Equipment	1 Phase 120/240 V	-	-	-	Ton
			nnected Tons	1.8 Tons	
Exhaust Fans	1 Phase 120/240 V	0.75	-	0.75	HP
Gas/Fuel/Sump Pump	1 Phase 120/240 V	-	-	-	HP
Small Motors (include motor codes)	1 Phase 120/240 V	1.5	-	1.5	HP
Air Compressor	1 Phase 120/240 V	-	-	-	HP
Swimming Pool	1 Phase 120/240 V	-	-	-	HP
Largest Motor (not included above) & code	3 Phase 277/480 V	200	-	200	HP
		Total c	onnected HP	202.25 HP	
Electric Heat	3 Phase 277/480 V	9.08	-	9.,08	kW
Water Heating	1 Phase 120/240 V	-	-	-	kW
Lighting	1 Phase 120/240 V	0.6	-	0.6	kW
Outlets	1 Phase 120/240 V	1.62	-	1.62	kW
Office Equipment	1 Phase 120/240 V	-	-	-	kW
Kitchen Equipment	1 Phase 120/240 V	-	-	-	kW
Computers, Magnetic Power Supplies	1 Phase 120/240 V	1.0	-	1.0	kW
Machinery	1 Phase 120/240 V	-	-	-	kW
Thermoplastic Injection Equipment	1 Phase 120/240 V	-	-	-	kW
Elevators	1 Phase 120/240 V	-	-	-	kW
Boiler	1 Phase 120/240 V	-	-	-	kW
Snow Melting	1 Phase 120/240 V	-	-	-	kW
Signs	1 Phase 120/240 V	-	-	-	kW
X-Ray Equipment	1 Phase 120/240 V	-	-	-	kW
Washer/Dryer	1 Phase 120/240 V	-	-	-	kW
Miscellaneous	1 Phase 120/240 V	1.0	-	1.0	kW
Heat Exchanger	1 Phase 120/240 V	-	-	-	kW
Humidifier	1 Phase 120/240 V	-	-	-	kW
Future	1 Phase 120/240 V		-	0	kW
-		Total c	onnected kW	20.22 kW	
It is important to provide the most facilities and determine the custom					Corp's
Customer Signature			Date		

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

© 202

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

#### **GENERAL NOTES:**

- 1. REFER TO CONDUIT/CONDUCTOR TABLE FOR WIRE AND CONDUIT REQUIREMENTS.
- 2. REFER TO ELECTRICAL PLANS FOR ELECTRICAL EQUIPMENTS LOCATIONS.

#### **SHEET KEYNOTES:**

- 1. CONDUIT SIZE 4". COORDINATE WITH UTILITY COMPANY AS AS REQUIRED.
- 2. TRANSFORMER: PROVIDED AND INSTALLED BY UTILITY COMPANY. PAD BY CONTRACTOR.
- 3. 4"C, CONDUCTORS BY UTILITY COMPANY.
- 4. METER SOCKET: PROVIDED AND INSTALLED AS REQUIRED BY UTILITY COMPANY.
- 5. CT METERING ENCLOSURE: PROVIDED AND INSTALLED AS REQUIRED BY BY UTILITY COMPANY.
- 6. <u>MAIN SERVICE DISCONNECT:</u> 480VAC, 300A, 3-POLE CIRCUIT BREAKER IN NEMA 3R ENCLOSURE. LABEL AS "MAIN SERVICE DISCONNECT" AND AS REQUIRED BY NEC 110.24.
- 7. TRANSFORMER T-1: XXKVA, 480VAC PRIMARY, 208Y/120V SECONDARY.
- 8. REFER TO PANELBOARD SCHEDULE FOR WIRE IDENTIFICATION.
- 9. VFD CONDUCTORS: 3-350, IN 3"C (BELDEN 29534 OR APPROVED EQUAL).
- 10. 1"C, CONDUCTORS AS REQUIRED FOR ATS TO START/STOP THE GENERATOR.
- 11. BACKUP POWER GENERATOR: 230KW, 480VAC, 3-PH, 4-W DIESEL GENERATOR.
- 12. AUTOMATIC TRANSFER SWITCH: 480VAC, 400A, 3-PH,


HAIRSEN ALLEN & LUCE

SIGNED KBH RAFTED DAS HECKED KBH REVISIONS DATE AUGUST 2020



ELECTRICAL POWER ONE-LINE DIAGRAM

E601 089.29.100



### INSTRUMENTATION AND CONTROL ONE-LINE DIAGRAM A

	TABLE VFD						TABLE	GATE
CONDUIT	COND	UCTOR	CP-1 TO VFD		CONDUIT	CONDUCTOR		CP-1 TO GATE ACTUATOR
SIZE	QTY	SIZE	SIGNAL DESCRIPTION		SIZE	QTY	SIZE	SIGNAL DESCRIPTION
	1	#14	COMMON INPUT			1	#14	COMMON INPUT
	1	#14	COMMON OUTPUT			1	#14	COMMON OUTPUT
	1	#14	BACKSPIN TIME DELAY			1	#14	CLOSE COMMAND
	1	#14	FILTER CAPACITOR CONTROL		1"C	1	#14	GATE OPEN STATUS
	1	#14	SHUTDOWN RESET			1	#14	GATE CLOSED STATUS
	1	#14	VFD FAULT			1	#14	OPEN COMMAND
3/4"C	1	#14	VFD FILTER HIGH TEMP.					
3/4 C	1	#14	VFD HAND START/STOP					
	1	#14	VFD HIGH PRESSURE SHUTDOWN	TABLE GEN				CEN
	1	#14	VFD LOW LEVEL SHUTDOWN					GEN

POSITION SWITCHES

1	#14	VFD HAND START/STOP				
1	#14	VFD HIGH PRESSURE SHUTDOWN			TADLI	CEN
1	#14	VFD LOW LEVEL SHUTDOWN			TABL	
1	#14	VFD READY TO START	CONDUIT		DUCTOR	CP-1 TO GENERATOR
1	#14	VFD RUN	SIZE	QTY	SIZE	SIGNAL DESCRIPTION
1	#14	VFD RUNNING		1	#14	COMMON INPUT
			3/4"C	1	#14	GENERATOR RUNNING
1	CAT 6U	VFD ETHERNET	3/4 C	1	#14	GENERATOR FAULT
1	CAT 6U	MOTOR RTD TEMPERATURES				
1	CAT 6U	POWER MONITOR				

POSITION POSITION

		TA	BLE ATS
CONDUIT	CON	DUCTOR	CP-1 TO ATS SIGNAL DESCRIPTION
SIZE	QTY	SIZE	CF-1 TO A 15 SIGNAL DESCRIPTION
	1	#14	COMMON INPUT
3/4"C	1	#14	ATS IN GENERATOR POSITION
3/1 C	1	#14	ATS IN UTILITY POSITION

TABLE CP-2												
CONDUIT	COND	JCTOR	CP-1 TO CP-2 SIGNAL									
SIZE	QTY	SIZE	DESCRIPTION									
	1	#14	COMMON OUTPUT									
	1	#14	COMMON INPUT									
3/4"C	1	#14	EXHAUST FAN ON									
	1	#14	EXHAUST FAN RUN									

POLE

CARD READER J-BOXES AND CONDUITS

POLE

POLE

POLE

FUTURE CCTV CONDUITS & J-BOXES

IDENT.	CONDUIT	CON	IDUCTOR	SIGNAL DESCRIPTION
IDENT.	SIZE	QTY	SIZE	SIGNAL DESCRIPTION
1A	3/4"	1	#18TSP	1 ANALOG SIGNAL
2A	3/4"	2	#18TSP	2 ANALOG SIGNALS
3 <b>A</b>	3/4"	3	#18TSP	3 ANALOG SIGNALS
TOUNT	CONDUIT	CON	DUCTOR	SIGNAL DESCRIPTION
IDENT.	SIZE	QTY	SIZE	SIGNAL DESCRIPTION
1D	3/4"	2	#14	1 SIGNAL
2D	3/4"	3	#14	1 COMMON, 2 DISCRETE SIG.
3D	3/4"	4	#14	VARIES
4D	3/4"	5	#14	VARIES

CONDUIT	CON	DUCTOR	CP-1 TO RTU
SIZE	QTY	SIZE	CP-1 TO KIU
3/4"C	1	CAT 6U	ETHERNET
3/4 C			

WALL

WALL

SIZE

				ſ	CONDUIT		NDUCTOR	CP-1 TO SECURITY ENCLOSURE
					SIZE	QTY	SIZE	SIGNAL DESCRIPTION
		TΔR	SLE PC			1	#14	COMMON INPUT
CONDUIT	COM		CP-1 TO PELLET CHLORINATOR			1	#14	COMMON OUTPUT
SIZE	CONDUCTOR OF THE PROPERTY OF T					1	#14	CHLORINE ROOM DOOR POS.
	1	#14	COMMON INPUT			1	#14	CLOSE COMMAND
	1	#14	COMMON OUTPUT			1	#14	GATE CLOSED STATUS
	1	#14	CHLORINATOR REMOTE RUN		4 4 100	1	#14	GATE OPEN STATUS
-	1				1-1/2C	1	#14	OPEN COMMAND
	1	#14	PUMP RUNNING			1	#14	SITE MOTION SENSOR ALARM
3/4"C	1	#14	SOLUTION TANK HIGH LEVEL			2	#14	WELL ROOM MAINT, DOOR POS.
	1	#14	SOLUTION TANK LOW LEVEL			1	#14	WELL ROOM MAN DOOR POS.
	1	#14	SPARE			1	#14	WELL ROOM ROOF HATCH POS.
	1	#14	WEIGHT SCALE ALARM			1	#14	WELL ROOM ROOF HATCH POS.
				L				
	1	#18TSP	WELL FLOW		1"C	-	-	FUTURE ETHERNET
3/4"C				L	- 0			

WALL

TABLE ASH-1 CONDUCTOR CP-1 TO ASH-1 SIGNAL

TABLE SECURITY

#14 COMMON OUTPUT #14 COMMON INPUT 1 #14 CHLORINE LEAK ALARM 1 #14 CHLORINE ALARM RESET

FUTURE MOTION SENSOR CONDUITS & J-BOXES

QTY SIZE

WALL

DESCRIPTION

SCADA COO	RDINATION	
SCADA CONTRACTO	OR: APCO, INC.	
CONTACT INFORMATI	ON: (801) 519-9500	
ENCLOSURE	SUPPLIED BY:	INSTALLED BY:
ENCLOSURE	CONTRACTOR	CONTRACTOR
INTERNAL PANEL	CONTRACTOR	CONTRACTOR
INTERNAL COMPONENTS	SCADA CONTR.	SCADA CONTR.
INTERNAL COMPONENT WIRING	SCADA CONTR.	SCADA CONTR.
ING TO/FROM RTU ENCLOSURE	SUPPLIED BY:	INSTALLED BY:
POWER SOURCE	CONTRACTOR	CONTRACTOR
FIELD I/O TO ENCLOSURE TERMINALS	CONTRACTOR	CONTRACTOR
FIELD DEVICE TERMINATIONS	CONTRACTOR	CONTRACTOR
COMPONENT	SUPPLIED BY:	INSTALLED BY:
PROGRAMMABLE LOGIC CONTROLLER	SCADA CONTR.	SCADA CONTR.
SEPARATE RTU CONTROLLER	-	-
	-	-
RNAL WIRING INSIDE RTU	SUPPLIED BY:	INSTALLED BY:
FIELD DEVICE WIRING TERMINATION	-	SCADA CONTR.
SIGNA L	SUPPLIED BY:	INSTALLED BY:
1" CONDUIT FOR SCADA RADIO	CONTRACTOR	CONTRACTOR
DATA RADIO COAXIAL CABLE	SCADA CONTR.	SCADA CONTR.
ANTENNA SUPPORT (SEE PLANS)	CONTRACTOR	CONTRACTOR
DATA RADIO ANTENNA	SCADA CONTR.	SCADA CONTR.



DESIGNED KBH	3					SCALE
DRAFTED DAS	2					
CHECKED KBH	1					
DATE AUGUST 2020	NO.	DATE	R E V I S I O N S	BY	APVD.	



WEST	JORDAN	CITY	WELL	#8	
ELEC	ΓRICAL				
I&C	DIAGRAM				

© 202

3/4"C

HANSEN ALLEN & LUCE


PANEL

SWITCH

1 #18TSP VFD COMMAND SPEED

P. STRING SPARE CONDUIT

1 #18TSP VFD RUNNING SPEED



#### FOLIPMENT SCHEDULE

			F	ЭПТРМІ	ENT RATIN	ıG				זמ	SCONN	IFCT		STA	RTER	
ITEM	DESCRIPTION			QUL 1 11										TYPE	NEMA	NOTES
		VOLTS	PH	HP	WATTS	FLA	MCA	AMPS	VOLTS	POLES	NEMA	FUSE	CONNECTION		SIZE	WOILS
AIT-2	CHLORINE ANALYZER	120	1	-	10	0.08			-	-	-	-	HARD-WIRED	-	-	
AIT-3	TURBIDITY ANALIZER	120	1		150	1.25		-	-	-	-	-	HARD-WIRED	-	-	
ATS /	AUTOMATIC TRANSFER SWITCH	480	3	-	-	400	-	-	-	-	-	-	HARD-WIRED	-	-	
CP-1	MAIN CONTROL PANEL	120	1	-	800	-	-	-	-	-	-	-	HARD-WIRED	-	-	
CP-2	EXHAUST FAN CONTROL PANEL	120	1	-	-	-	-	-	-	-	-	-	HARD-WIRED	-	-	
CTE	CURRENT TRANSFORMER ENCLOSURE	480	3	-	-	-	-	-	-	-	-	-	-	-	-	
FE-1	FLOW ELEMENT	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
FIT-1	FLOW INDICATOR/TRANSMITTER	120	1	-	50	0.4										
GA-1 (	GATE ACTUATOR	240	1	1	1,920	8	-	-	-	-	-	-	-	-	-	
GEN I	BACKUP POWER GENERATOR	480	3	-		-	-	-	-	-	-	-	HARD-WIRED	-	-	
LT-1	WELL LEVEL TRANSMITTER	24	-	-	-	-	-	-	-	-	-	-	-	-	-	
MSD [	MAIN SERVICE DISCONNECT	480	3	-	-	-	-	-	-	-	-	-	-	-	-	
P-1 \	WELL PUMP	480	3	200	199,296	240	-		-	-	-	-	HARD-WIRED	VFD	200 HP	
PC-1	PELLET CHLORINATOR	120	1	-	1,656	-	-	-	-	-	-	-	-	-	-	
RTU I	REMOTE TELEMETRY UNIT	120	1	-	-	-	-	-	-	-	-	-	HARD-WIRED	-	-	
SV-2	WELL PRE-LUBE SOLENOID VALVE	120	-	-	-	-	-	-	-	-	-	-	-	-	-	
TT-1	PUMP ROOM TEMPERATURE SENSOR	24	-	-	-	-	-	-	-	-	-	-	-	-	-	
TT-2 (	CHLORINE ROOM TEMPERATURE SENSOR	24	-	-	-	-	-	-	-	-	-	-	-	-	-	
V-1	WASTE VALVE ACTUATOR	120	1	1/6	528	4.4		-	-	-	-	-	-	-	-	
V-2	SYSTEM VALVE ACTUATOR	120	1	1/6	528	4.4		-	-	-	-	-	-	-	-	
VFD \	WELL VARIABLE FREQUENCY DRIVE	480	3	200	-	-		-	-	-	-	-	HARD-WIRED		-	

NOTES: 1)

#### ETYTLINE COUEDINE

			-IXTURE SCHEDULE						
TYP	DESCRIPTION		MANUFACTURER	FIX	LAMP	LUMENS	TEMPERATURE	MOUNTING	NOTES:
	DESCRIPTION	NAME	CATALOG NO.	VA	Dun	LOTTERIO	(KELVIN)	TIOOHI IIIO	HOTES.
F1	4' LED ENCLOSED INDUSTRIAL, FIBERGLASS	METALUX	4VT2 LD5-4-DR-UNV-L840-CD1-WL-U	38	LED	4000	4000	SURFACE	
	HOUSING, DAMP LOCATION, MVOLT								
F2	LED WALL MOUNTED FULL CUTOFF MINI	LUMARK	XTOR2B-W-PC1	18	LED	1,472	4000	WALL	1)
	AREA WALL PACK FOR WET LOCATIONS								
F3	FLOOD LIGHT, WIDE DISTRIBUTION, 120 VAC, 4000 DEG K LED	EATON	UFLD-C25-E-U-66-Y-BZ	128	LED	15,530	4000	WALL	2)
F4#	WEST JORDAN STANDARD POLE LIGHT	-	-	129	LED	13,748	4999	POLE	3)
F4E	WEST JORDAN STANDARD LIGHT POLE	-	-	-	-	=	-	=	3)

- 1) FIXTURE SHALL BE MOTION SENSOR CONTROLLED.
- 2) AIM TOWARD GENERATOR SIDE AISLE.
- POLE AND FIXTURE SHALL BE PURCHASED FROM WEST JORDAN CITY.

#### HVAC MECHANICAL FOUIPMENT SCHEDULE

	• • • • • • • • • • • • • • • • • • • •			-0	, .,	·	THE TIEST WITH E EQUIT TENT SOILE FOLE													
														STARTER						
ITEM	DESCRIPTION	EQUIPMENT RATING							DIS	CONNEC	T			TYPF	NEMA	NOTES				
		VOLTS	PH	HP	WATTS	FLA	MCA	AMPS	VOLTS	POLES	NEMA	FUSE	CONNECTION	ITPE	SIZE	NOTES				
CU-1	CONDENSING UNIT	208	1		3,162	15.2	19	30	240	3	3R	25	HARD-WIRED	INCL.	N/A					
CU-2	CONDENSING UNIT	208	1	-	3,162	15.2	19	30	240	3	3R	25	HARD-WIRED	INCL.	N/A					
EF-1	EXHAUST FAN	120	1	F	150	1.25	-	20	125	1	-	-	HARD-WIRED	N/A	N/A					
FC-1	AIR HANDLER	208	1		-	-	-	-	-	-	-	-	-	-	-	1)				
FC-2	AIR HANDLER	208	1		-	-	-	-	-	-		-	-	-	-	1)				
L-1	CHL. ROOM INTAKE LOUVER	120	1	F	50	0.4	-	-	-	-	-	-	-	-	-					
L-2	CHL. ROOM EXHAUST LOUVER	120	1	F	50	0.4	-	-	-	-	-	-	-	-	-					
UH-1	UNIT HEATER	480	3	F	5,000	6.02	-	-	-	-	-	-	HARD-WIRED	INCL.	N/A					
UH-2	UNIT HEATER	480	3	F	3,300	3.97	-	30	600	3	1	-	HARD-WIRED	N/A	N/A					

NOTES: 1) INDOOR UNIT RECEIVES POWER FROM OUTDOOR UNIT. REFER TO MANUFACTURER'S LITERATURE.

#### PANELBOARD H LOCATION: WELL ROOM MFGR: SQUARE D COMPANY VOLTS: 480Y/277 DIMENSIONS: 20"Wx 6"Dx 26"H TYPE: I-LINE X M.L.O PHASE: 3 MOUNTING: SURFACE NEMA: 1 22,000 A.I.C. WIRES: 4 FEED: TOP X SURGE PROTECTION FED FROM: UTILITY PHASE LOADS CIRCUIT CONT. N-CONT. DESCRIPTION ID WATTS WATTS NO CONT. N-CONT. CONT. N-CONT. CONT. N-CONT. 20 3 CP-1 SURGE DEVICE 199,296 66,432 350 3 WELL PUMP (200 HP) 310 66,432 0 66,432 20 3 WELL ROOM HEATER 312 5,000 1,667 1,667 1,667 20 3 CHLORINE ROOM HEATER 312 3,300 1,100 1,100 1,100 20 3 PELLET CHLORINATOR 312 2,491 830 830 830 50 3 TRANSFORMER L 5,382 14,482 6 1,954 5,071 860 4,221 2,568 5,191 SPACE 71,983 5,071 70,889 4,221 72,597 5,191 TOTAL WATTS: 215,469 14,482 CONTINUOUS LOAD: 215,469 CONTINUOUS LOAD \* 125%: 269,337 NON-CONTINUOUS LOAD: 14,482 DESIGN WATTS: 283,819 MIN. RATING (AMPS):

#### TRANSFORMER L

LOCATION: WELL ROOM		25.5 PRIMARY AMPS				PRIMARY VOLTS: 480			
DIMENSIONS: 14.75"W x 9.00"D x 14.75"H	ENSIONS: 14.75"W x 9.00"D x 14.75"H 58.9 SECONDARY AMPS								
MOUNTING: WALL KVA: 30									
FEED: SIDE						FED FROM: I	PNL H		
					PHASE	LOADS			
	CONT.	N-CONT.	Α		В		C		
	WATTS	WATTS	CONT.	N-CONT.	CONT.	N-CONT.	CONT.	N-CONT.	
PANELBOARD L	5,382	14,482	1,954	5,071	860	4,221	2,568	5,19	
TOTAL WATTS:	5,382	14,482	1,954	5,071	860	4,221	2,568	5,19	
CONTINUOUS LOAD:	5,382								
CONTINUOUS LOAD * 125%:	6,728								
NON-CONTINUOUS LOAD;	14,482								
DESIGN WATTS:	21,210								

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

© 2020

HEGERHORST POWER ENGINEERING INCORPORATED
708 EAST 50 SOUTH
AMERICAN FORK, UT 84003

HPE PROJECT 20.025 FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

#### **GENERAL NOTES:**

1. NOT USED.

#### **SHEET KEYNOTES:**

1. GATE SUPPLIED 208V, 1-PHASE. IF GATE REQUIRES 240V 1-PHASE PROVIDE APPROPRIATE BUCK/BOOST TRANSFORMER IN WELL BUILDING AS REQUIRED. COORDINATE WITH GATE ACTUATOR SUPPLIER DURING CONSTRUCTION.

PANEL BOARD I


							Ρ.	ANELE	BOARD	L								
LOCAT	TON: WELL ROOM	MFGR:	SQUARE D					225	AMPS					VOLTS:	208Y/1	20		
DIMEN	SIONS: 20"W x 5.75"D x "H	TYPE:	NQ					90	M.C.B.					PHASE:	3			
MOUN	TING: SURFACE	NEMA:	1					10,000	A.I.C.					WIRES:	4			
FEED:	TOP							Χ	SPD				F	ED FROM:	XFMR L			
								PHASE	LOADS									
BRK	R	CIRCUIT	CONT.	N-CONT.		Α		В		C			N-CONT.	CONT.	CIRCUI	Г	BR	KR
Α	P DESCRIPTION	ID	WATTS	WATTS	NO	CONT.	N-CONT.	CONT.	N-CONT.	CONT.	N-CONT.	NO	WATTS	WATTS	ID	DESCRIPTION	Α	Р
20	1 CO, PUMP ROOM	212		1,080	1	1,000	1,080					2		1,000	212	CP-1/RTU	20	1
20	1 CO, CHLORINE ROOM	212		180	3			500	180			4		500	212	RTU RADIO ENCLOSURE	20	1
20**	1 CO, EXTERIOR	212		360	5					0	1,110	6	750		212	GENERATOR JACKET WATER HEATER	20	2
20**	1 LTS, INTERIOR	212	304		7	304	750					8	750		-	-	-	-
20	1 LTS, EXTERIOR	212	310		9			310	1,000			10	1,000		212	GENERATOR BATTERY CHARGER	20	1
20	1 FLOW METER	212	50		11					50	1,581	12	1,581		20	WELL ROOM EXTERIOR A/C UNIT-1	30	2
20	2 SITE GATE ACTUATOR	212		960	13	0	2,541					14	1,581		-	-	-	-
-	-	-		960	15			0	2,541			16	1,581		20	WELL ROOM EXTERIOR A/C UNIT-1	30	2
20	1 TURBIDIMETER	212	150		17					150	1,581	18	1,581		-	-	-	-
20	1 RESIDUAL CHLORINE ANALYZER	212	150		19	150	500					20	500		212	V-1 ACTUATOR	20	1
20**	1 CO, IRRIGATION CONTROLLER	212	50		21			50	500			22	500		212	V-2 ACTUATOR	20	1
20	1 LTS, POLES & CCTV CO	212	512	720	23					2,368	920	24	200	1,856	20	CP-2 CONTROL PANEL	30	1
20	1 SECURITY ENCLOSURE	212	500		25	500	200					26				SPARE	20	1
20	1 SPARE				27			0	0			28				SPARE	20	1
	1 SPACE				29					0	0	30				SPARE	20	1
	TOTAL WATTS:		2,026	4,260		1,954	5,071	860	4,221	2,568	5,191		10,022	3,356				
	CONTINUOUS LOAD:		5,382															
	CONTINUOUS LOAD * 125%:		6,728															
	NON-CONTINUOUS LOAD:		14,282		** P	PROVIDE A G	FC CIRCUIT	BREAKER										
	DESIGN WATTS:		21,010															
	MIN. RATING (AMPS):		58															



DESIGNED KBH	3					
DRAFTED <b>DAS</b>	2					l
CHECKED <b>KBH</b>	1					l
DATE AUGUST 2020	NO.	DATE	REVISIONS	BY	APVD.	




SCALE



## CONTROL PANEL CP-1 WITH RTU 1





# NAMEPLATE DETAIL A

SCADA COOF	RDINATION	
SCADA CONTRACTO	DR: APCO, INC.	
CONTACT INFORMATIO	N: (801) 519-9500	
ENCLOSURE	SUPPLIED BY:	INSTALLED B
ENCLOSURE	CONTRACTOR	CONTRACTO
INTERNAL PANEL	CONTRACTOR	CONTRACTO
INTERNAL COMPONENTS	SCADA CONTR.	SCADA CONT
INTERNAL COMPONENT WIRING	SCADA CONTR.	SCADA CONT
ING TO/FROM RTU ENCLOSURE	SUPPLIED BY:	INSTALLED B
POWER SOURCE	CONTRACTOR	CONTRACTO
FIELD I/O TO ENCLOSURE TERMINALS	CONTRACTOR	CONTRACTO
FIELD DEVICE TERMINATIONS	CONTRACTOR	CONTRACTO
COMPONENT	SUPPLIED BY:	INSTALLED B
PROGRAMMABLE LOGIC CONTROLLER	SCADA CONTR.	SCADA CONT
SEPARATE RTU CONTROLLER	-	-
	-	-
RNAL WIRING INSIDE RTU	SUPPLIED BY:	INSTALLED B
FIELD DEVICE WIRING TERMINATION	-	SCADA CONT
SIGNA L	SUPPLIED BY:	INSTALLED B
1" CONDUIT FOR SCADA RADIO	CONTRACTOR	CONTRACTO
DATA RADIO COAXIAL CABLE	SCADA CONTR.	SCADA CONT
ANTENNA SUPPORT (SEE PLANS)	CONTRACTOR	CONTRACTO
DATA RADIO ANTENNA	SCADA CONTR.	SCADA CONT

### CP-1 MAIN CONTROL PANEL I/O LIST

DISCRETE IN	IPUTS		
DESCRIPTION	FROM	TO	NOTES
ATS IN GENERATOR POSITION	ATS	CP-1	
ATS IN UTILITY POSITION	ATS	CP-1	
CHLORINE PUMP ON	PC-1	CP-1	
CHLORINE RM. EF RUNNING	CP-2	CP-1	
CHLORINE ROOM DOOR OPEN	SEC. PNL.	CP-1	
CHLORINE SOLUTION TANK HIGH LEVEL	PC-1	CP-1	
CHLORINE SOLUTION TANK LOW LEVEL	PC-1	CP-1	
CHLORINE SYSTEM FLOW	PC-1	CP-1	
CHLORINE WEIGHT SCALE ALARM	PC-1	CP-1	
CP-1 POWER LOSS	CP-1	CP-1	
GATE CLOSED STATUS	SEC. PNL.	CP-1	
GATE OPEN STATUS	SEC. PNL.	CP-1	
GENERATOR FAULT	GEN	CP-1	
GENERATOR ON	GEN	CP-1	
PELLET CHLORINATOR ALARM	PC-1	CP-1	
PELLET CHLORINATOR ON	PC-1	CP-1	
SYSTEM VALVE FULL CLOSED POSITION	V-2	CP-1	
SYSTEM VALVE FULL SYSTEM POSITION	V-2	CP-1	
VFD ALARM RESET	VFD	CP-1	
VFD FAULT	VFD	CP-1	
VFD FILTER HIGH TEMPERATURE	VFD	CP-1	
VFD HOA IN AUTO MODE	VFD	CP-1	
VFD HOA IN HAND MODE	VFD	CP-1	
VFD ON	VFD	CP-1	
VFD READY-TO-START	VFD	CP-1	
VFD SHUTDOWN RESET	VFD	CP-1	
WASTE VALVE FULL CLOSED POSITION	V-1	CP-1	
WASTE VALVE FULL WASTE POSITION	V-1	CP-1	
WELL HIGH DISCHARGE PRESSURE	PSH-1	CP-1	
WELL ROOM FLOOR HIGH WATER	LSH-3	CP-1	
WELL ROOM MAINTENANCE DOOR A OPEN	SEC. PNL.	CP-1	
WELL ROOM MAINTENANCE DOOR B OPEN	SEC. PNL.	CP-1	
WELL ROOM MAN DOOR OPEN	SEC. PNL.	CP-1	
WELL ROOM ROOF HATCH OPEN	SEC. PNL.	CP-1	
WELL STOP	RTU	CP-1	

DISCRETE OU	TPUTS -		
DESCRIPTION	FROM	ТО	NOTES
CHLORINE RM EXHAUST FAN RUN	CP-1	CP-2	
GATE CLOSE COMMAND	CP-1	SEC. PNL.	
GATE OPEN COMMAND	CP-1	SEC. PNL.	
PELLET CHLORINATOR REMOTE RUN	CP-1	PC-1	
PRE-LUBE SOLENOID VALVE OPEN	CP-1	SV-2	
SYSTEM VALVE OPEN COMMAND	CP-1	V-2	
VFD BACKSPIN TIME DELAY	CP-1	VFD	
VFD FILTER CAPACITOR CONTROL	CP-1	VFD	
VFD HP SHUTDOWN & INDICATION LIGHT	CP-1	VFD	
VFD LOW LEVEL SHDN & INDICATION LIGHT	CP-1	VFD	
VFD RUN	CP-1	VFD	
VFD SHUTDOWN	CP-1	VFD	
WASTE VALVE CLOSE COMMAND	CP-1	V-1	
NOTES: 1)			

ANALOG INPUTS

ANALOG INPUTS										
DESCRIPTION	FROM	TO	NOTES							
CHLORINE ROOM TEMPERATURE	TT-2	CP-1	1)							
RES IDUAL CHLORINE	AIT-2	CP-1	1)							
STATION DISCHARGE PRESSURE	PT-1	CP-1	1)							
VFD RUNNING SPEED	VFD	CP-1	1)							
WELL DISCHARGE FLOW	FIT-1	CP-1	1)							
WELL LEVEL	LT-1	CP-1	1)							
WELL DISCHARGE PRESSURE	PT-2	CP-1	1)							
WELL ROOM TEMPERATURE	TT-1	CP-1	1)							
WELL TURBIDITY	AIT-3	CP-1	1)							
NOTES:										

NOTES: 1)

SCALE

1) SIGNAL SHALL BE REPEATED AS PLC ANALOG OUTPUT TO RTU.

ANALOG OUTPUTS										
DESCRIPTION	FROM	TO	NOTES							
CHLORINE DOSE RATE (WELL FLOW)	CP-1	PC-1								
VFD COMMAND SPEED	CP-1	VFD								

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025

FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

#### **GENERAL NOTES:**

INTERNAL COMPONENTS AND ARRANGEMENT NOT SHOWN ON THESE DRAWINGS AND SHALL BE PROVIDED BY APCO, THE CITY'S SCADA CONTRACTOR. APCO SHALL PROVIDE ALL INTERNAL COMPONENTS AND ALL PLC AND HMI PROGRAMMING.

#### **SHEET KEYNOTES:**

- 1. 10" OPERATOR TOUCH SCREEN SHOWN. PROVIDED AND INSTALLED BY SCADA CONTRACTOR.
- 2. TYPICAL MAIN CONTROL PANEL SHOWN. MODIFY AS REQUIRED BY OWNER.
- 3. VFD READY—TO—START INDICATION AND START PUSHBUTTON.
- 4. CONTROL POWER INDICATION AND OFF/ON SELECTOR SWITCH.

(TYPICAL CONTROL PANEL)






DESIGN	ed <b>KBH</b>	3					
DRAFTE	D DAS	2					
CHECK	ed <b>KBH</b>	1					ı
DATE	AUGUST 2020	NO.	DATE	REVISIONS	BY	APVD.	ı




HANSEN ALLEN & LUCEne




#### NOTES:

- 1. CONTRACTOR SHALL ASSIGN FUSE, RELAY, TERMINAL AND WIRE
- 2. CONTRACTOR MAY COMBINE CONDUCTORS IN COMMON CONDUIT TO DEVICES IN SAME PROXIMITY.
- 3. PROVIDE AN INTERPOSING RELAY AND WIRE RELAY CONTACT TO PLC INPUT AS INDICATED.
- 4. CONTRACTOR SHALL ASSIGN PLC MODULE AND CHANNEL.



#### INTERPOSE RELAY LOGIC




PLC DISCRETE INPUT LOGIC



#### NOTES:

- 1. CONTRACTOR SHALL ASSIGN FUSE, RELAY, TERMINAL AND WIRE NUMBERS AS REQUIRED.
- 2. CONTRACTOR SHALL ASSIGN PLC MODULE AND




PLC ANALOG OUTPUT

PLC DISCRETE OUTPUT WIRING 3

#### NOTES:

- CONTRACTOR SHALL ASSIGN FUSE, RELAY, TERMINAL AND WIRE NUMBERS AS REQUIRED.
- 2. CONTRACTOR SHALL ASSIGN PLC MODULE AND CHANNEL.




PLC ANALOG INPUT WIRING 2


#### NOTES:

REVISIONS

- CONTRACTOR SHALL ASSIGN FUSE, RELAY, TERMINAL AND WIRE NUMBERS AS REQUIRED.
- 2. CONTRACTOR SHALL ASSIGN PLC MODULE AND CHANNEL.
- 3. PROVIDE AN INTERPOSING RELAY AND WIRE RELAY CONTACT TO PLC INPUT AS INDICATED.



PLC DISCRETE OUTPUT LOGIC



PLC ANALOG OUTPUT WIRING 4


FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORS'

#### **GENERAL NOTES:**

HEGERHORST POWER ENGINEERING INCORPORATED 708 EAST 50 SOUTH AMERICAN FORK, UT 84003

HPE PROJECT 20.025

- 1. REFER TO E605 FOR TYPICAL CONTROL PANEL ARRANGEMENT.
- 2. KEYNOTES SHOWN AT EACH PLC MODULE DIAGRAM.




ETHERNET SIGNAL DIAGRAM


RAFTED DAS HECKED KBH ATE AUGUST 2020

**WEST JORDAN** 

WEST JORDAN CITY WELL #8 **ELECTRICAL** CP-1 CONTROL DIAGRAM SHT. 2 E607 089.29.100



- (1) VFD MEMBRAIN KEYPAD
- 2 VFD E-STOP MUSHROOM HEAD LATCHING PUSHBUTTON
- 3 VFD STATUS INDICATION LIGHT
- 4 VFD FAULT INDICATION LIGHT
- 5 VFD OFF INDICATION LIGHT
- 6 HIGH DISCHARGE PRESSURE SHUTDOWN INDICATION LIGHT
- 7 HAND-OFF-AUTO SELECTOR SWITCH
- 8 ALARM RESET PUSHBUTTON
- 9 POWER AND ENERGY METER (COMPTON INTEGRA 1530)
- 10 VFD SPEED POTENTIOMETER
- 1 LOW LEVEL SHUTDOWN INDICATION LIGHT
- 12 START PUSH BUTTON



CP-2 EXHAUST FAN CONTROL PANEL 1

H.P.E. INC. ELECTRICAL ENGINEERS
POWER SYSTEMS, CONTROL & INSTRUMENTATION SYSTEMS

POWER SYSTEMS, CONTROL & INSTRUMENTATION
HEGERHORST POWER ENGINEERING INCORPORATED
708 EAST 50 SOUTH
AMERICAN FORK, UT 84003

AMERICAN FORK, UT 84003 HPE PROJECT 20.025


FOR INFORMATION ABOUT THIS JOB, PLEASE CONTACT: KEITH HEGERHORST

#### **GENERAL NOTES:**

- ENCLOSURE DIMENSIONS SHOWN ARE TYPICAL AND SHALL BE MODIFIED BY THE CONTRACTOR AS REQUIRED FOR THE DEVICES USED.
- 2. WIRING DIAGRAM IN TYPICAL. MODIFY AS REQUIRED.

#### **SHEET KEYNOTES:**

1. OFF-ON TOGGLE SWITCH WITH ROOM LIGHT SWITCH.





EXHAUST FAN WIRING DIAGRAM B





WEST JORDAN CITY WELL #8
ELECTRICAL
CP-2 EXHAUST FAN CONTROL PANEL

E608

FILE NAME: FILE DATE:

HANSEN ALLEN & LUCEnc